


# EZ-Bend® 3.0 Cable



A Furukawa Company

The **EZ-Bend® 3.0 Cable**, available in riser, plenum, and low-smoke zero-halogen constructions, **can be routed around corners and deployed** using traditional fast and easy copper wire installation practices, with negligible signal loss\*. Ideal for aggressive routing environments where space is at a premium, the EZ-Bend 3.0 Cable offers **reliable support for MDU and in-home wiring applications**.



*EZ-Bend 3.0 Optical Cable Cross-Section*

## Features:

- 3.0 diameter ruggedized simplex cordage
- Less than 0.1 dB macrobending attenuation at 1550 nm for 1 turn at 5 mm fiber bend radius
- Solid construction fiber with macrobending performance far better than ITU G.657B requirements
- Backward compatible with installed G.652D fibers
- Available in alternative colors upon request
- Conform to UL® Riser and Plenum fire ratings
- Compliant with Telcordia 409 & ICEA S-83-596 requirements
- Featuring EZ-Bend Optical Technology, a breakthrough developed by OFS Labs



*EZ-Bend 3.0 Cable shown bend molding*

## Benefits:

- **“Copper-like” installation process:** Can be routed around corners using familiar copper wire practices\*
- **Faster, easier installation:** no extra steps to install bend limiters, conduits, or raceways
- **Compact installation and storage:** Conforms to building; slack fits in small storage spaces
- **Fast, easy, low loss splicing** to G.652D fiber with existing core and clad aligned splice equipment
- **Familiar, standard connector termination:** Solid fiber construction can be terminated using standard optical connectors and polishing techniques
- **Familiar connector endface cleaning** using same process as with existing G.652 solid construction fiber
- **MDU and in-home optimized:** Ideal for in-residence wiring and difficult installation routes in MDU overbuilds
- **Greener Solution:** Free of heavy metals and RoHS-compliant; solution uses less total materials and energy than copper solutions

\* 3.0 mm Cables are not recommended for stapling.

## Specifications

Cable Type	Jacket Color*	Part Number	Maximum Tensile Rating N (lb)	Nominal Weight kg/km (lb/100 ft)	Standard REELEX Box Length †
Riser	White	LG3.0C-001C-DRW	260 N (60 lb)	6.41 kg/km (0.43 lb/100 ft)	457.2 m (1500 ft)
Plenum	White	LG3.0C-001C-DPW	260 N (60 lb)	7.94 kg/km (0.53 lb/100 ft)	457.2 m (1500 ft)
Low-Smoke Zero Halogen	White	LG3.0C-001D-DHW	260 N (60 lb)	6.17 kg/km (0.42 lb/100 ft)	457.2 m (1500 ft)

\* Other colors available upon customer request.

† Alternative lengths available on standard premise spools. Contact OFS for more details.

### Example of Standard Sheath Marking [Custom sheath marking available upon request]

White-Jacketed Riser-Rated Ruggedized Drop Cable with EZ-Bend Technology

OFS EZ BEND ULTRA BEND INSENSITIVE OPTICAL DROP CABLE -C- LG3.0C-001C-DRW C(UL) US TYPE OFNR [CSA OFN FT4] {lot number} ~nnnnn FEET

## Performance

Flame Performance	Mechanical and Environmental Performance	Temperature Range
Riser: UL 1666 compliant	Telcordia GR-409, ICEA S-83-596 compliant	Installation: 32° F to 104° F (0° C to 40° C)
Plenum: NFPA 262 (UL 910) compliant		Operation: -40° F to 158° F (-40° C to 70° C)
Non-Halogen: IEC 60332-3c and IEC 61034-2 compliant		Storage: -40° F to 158° F (-40° C to 70° C)
Attenuation @	1310 nm	1550 nm
Maximum Attenuation	0.4 dB/km	0.3 dB/km
Typical Attenuation	0.35 dB/km	0.25 dB/km



Use electronic files, available at:  
[www.ofsoptics.com](http://www.ofsoptics.com) - Use less paper

EZ-Bend is a registered trademark of OFS FITEL, LLC.  
UL is a registered trademark of Underwriters Laboratories Inc.

For additional information please contact your sales representative. You can also visit our website at [www.ofsoptics.com](http://www.ofsoptics.com) or call 1-888-fiberhelp (1-888-342-3743) from inside the USA or 1-770-798-5555 from outside the USA.

OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice.

This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.

Copyright © 2011 OFS FITEL, LLC.  
All rights reserved, printed in USA.

OFS  
Marketing Communications  
fap-252-0811



A Furukawa Company