

Premises Jacket Color by Fiber Type

Application Note AN-956

The purpose of this document is to provide the reader with information regarding jacket colors for Premises cables and cordages. The jacket color is defined by the fiber type; however, custom color code is available upon request.

Standard Premises Jacket Colors by Fiber Type

Jacket Color	Subunit Color*	Fiber Type
Blue	Blue	AllWave® Flex Blue Tiger (200 kpsi)
Orange	Orange	50/125 Multimode (Standard and Laser Optimized 50 Micron)
Orange	Orange	62.5/125 Multimode (Standard, Laser Optimized and Laser Optimized 62.5/125 XL 62.5/125 XL)
Yellow	Yellow	Singlemode (AllWave®Zero Water Peak , AllWave® Flex Bend Optimized Zero Water Peak, TrueWave®RS, TrueWave® REACH, TrueWave®SRS and TrueWave®XL)
White	N/A	EZ Bend Ultra Bend Insensitive Singlemode <i>(White is default color for indoor applications only)</i>
Aqua	Aqua	LaserWave™ (LaserWave™ G+, LaserWave™ 300, LaserWave™500, LaserWave™550)
Black	Defined by fiber type. See above colors.	Black is the default color for AccuDry Indoor/Outdoor, 4.5mm Double Jacketed (IO4.5C) and 4.8 Simplex Indoor/Outdoor (IO4.8C) cables regardless of fiber type

*AccuMax®, AccuDry™ and Minicord® Breakout Cables with 18 fibers or more will contain subunits. Fiber counts of 18-24 contains 6 fibers per tube. Fiber counts > 24 contains 12 fibers per tube.

Premises cables and cordages consist of the following:

ACCUMAX® Building Cables	4.5mm Double Jacketed Indoor and Indoor/Outdoor Drop Cable
AccuDry™ Indoor/Outdoor Cables	4.8mm Simplex Indoor and Indoor/Outdoor Interconnect Cordage
Minicord® Break-Out Cables	Minicord® Cordage – 1.6mm (Simplex and Duplex)
AccuRibbon® Interconnect Cables	900 m Buffered Fiber
Enhanced AccuFLEX® PLUS Ribbon Cables	Strengthened Buffered Jacketed 900 m Buffer Fiber (with aramid)
Standard cordage – 2.9mm and 2.0mm (Simplex and Duplex)	600 m Buffered Fiber
3.2mm Duplex Round Riser Interconnect Cordage	
4.0mm Low Smoke Zero, Halogen Cordage	
MT Round Duplex Cordages	