

Fitel Battery Packs for Fusion Splicers and Accessories



S947B

Features and Benefits

- Long lasting
- Durable
- Overheat protection
- Overcharge protection
- Battery protection circuit
- Lightweight
- High capacity

Item	S947A / S947B	S943B / S943D	S946B	S944C
Splicer	S124M12/S179/S185	S123/S153/S178	NJ001/EZT-01	S218R/R-Plus/R-200
Battery Type	Lithium ion	Lithium ion	Lithium Polymer	Lithium ion
Cell Number	5	3	4	2
Capacity	S947A:3000mAh (55.5Wh) S947B:3350mAh (62Wh)	2600mAh (28.86Wh)	2000mAh (29.6Wh)	2040mAh (14.68Wh)
Nominal Voltage	18.5V	S943B: 11.1V S943D: 10.89V	14.8V	7.2V
Weight	260g	173g	145g	78g



For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com/fusion-splitters/ or call 866-452-9516.

Fusion Splicer Customer Service, Training and Service Center

Toll Free: 866-452-9516 Phone: 678-783-1090

Fax: 678-783-1093

Email: splitters@ofsoptics.com

Copyright © 2020 OFS Fitel, LLC.

All rights reserved, printed in USA.

OFS Corporate Headquarters

2000 Northeast Expressway Norcross, Georgia 30071, USA

Toll Free: 888-Fiber-Help

Intl. Phone: 770-798-5555

OFS Marketing Communications

Doc ID: FITELE Battery Packs Date: 12/20

"Bound to Innovate" and EZ-Terminator are registered trademarks of Furukawa Electric Co., Ltd. FITELE is a registered trademark of Furukawa Denki Kogyo Kabushiki Kaisha DBA Furukawa Electric Co., Ltd.

Furukawa reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Furukawa warranties or specifications relating to any of its products or services.